LISTING OF THE CLAIMS

Docket No.: 09852/0205611-US0

The claims are listed below as a courtesy to the Examiner. No amendment is made.

Claim 1 (**Previously Presented**): A moisture-curable polyurethane hot-melt adhesive, which comprises urethane prepolymer obtained by a reaction between polyisocyanate and polyols, wherein the polyols comprise:

long-chain aliphatic polyester polyol (A) represented by a general formula (I); aliphatic polyether polyol (B) having a number average molecular weight of 3,000 to 15,000; and aromatic polyester polyol (CI) which has a number average molecular weight of 1,000 to 5,000 and has a glass-transition temperature of 40°C or more.

$$\begin{bmatrix}
R^{1} & O & R^{2} & O \\
R^{1} & O & O
\end{bmatrix}_{\mathbf{n}} O H$$
(I)

(In the general formula (I), R^1 and R^2 each independently represents a straight chain alkylene group wherein the number of carbon atoms in the group is an even number, the sum of the number of carbon atoms in R^1 and R^2 is 12 or more, and n represents a number of 3 to 40.)

Claim 2 (**Previously Presented**): The moisture-curable polyurethane hot-melt adhesive according to claim 1, wherein the polyols further comprise aromatic polyesterpolyol (CII) which has a number average molecular weight of 400 to 3,500 and a glass-transition temperature of 20°C or less.

Claim 3 (**Original**): The moisture-curable polyurethane hot-melt adhesive according to claim 1, wherein the aliphatic polyetherpolyol (B) is a polypropylene glycol or polybutylene glycol, which has a number average molecular weight of 3,000 to 15,000.

Docket No.: 09852/0205611-US0

Claim 4 (**Original**): The moisture-curable polyurethane hot-melt adhesive according to claim 1, wherein the aliphatic polyetherpolyol (B) is ethylene oxide denatured polypropylene glycol or ethylene oxide denatured polybutylene glycol, which is obtained by adding ethylene oxide to both terminal ends of polypropylene glycol or polybutylene glycol.

Claim 5 (**Previously Presented**): The moisture-curable polyurethane hot-melt adhesive according to claim 4, wherein the aliphatic polyetherpolyol (B) comprises 20% by mass or less of structural units originating from ethylene oxide based on the total amount of the aliphatic polyetherpolyol (B).

Claim 6 (**Previously Presented**): The moisture-curable polyurethane hot-melt adhesive according to claim 1, wherein the adhesive is obtained by a reaction of the polyisocyanate and the polyols, which comprises 20 to 60 parts by mass of the long-chain aliphatic polyester polyol (A), 5 to 40 parts by mass of the aliphatic polyether polyol (B) and 5 to 25 parts by mass of the aromatic polyester polyol (CI) based on 100 parts by mass of the total amount of the polyol and the polyisocyanates.

Claim 7 (**Original**): The moisture-curable polyurethane hot-melt adhesive according to claim 2, wherein

the adhesive is obtained by a reaction of the polyisocyanate and the polyols, which comprises 20 to 60 parts by mass of the long-chain aliphatic polyester polyol (A), 5 to 40 parts by mass of the aliphatic polyether polyol (B), 5 to 20 parts by mass of the aromatic polyester polyol (CI) and 5 to 20 parts by mass of the aromatic polyesterpolyol (CII), wherein the sum of the polyols

Docket No.: 09852/0205611-US0

(CI) and (CII) is in the range of 10 to 35 parts by mass, based on 100 parts by mass of the total

amount of the polyol and the polyisocyanates.

Claim 8 (Previously Presented): The moisture-curable polyurethane hot-melt adhesive

according to claim 1, wherein the urethane prepolymer comprises an island like phase separated

structure.

Claim 9 (Original): The moisture-curable polyurethane hot-melt adhesive according to

claim 1, wherein the melt viscosity at 125°C of the adhesive is in the range of 2,000 to 9,000

mPa · s.

Claim 10 (Original): A decorative fixture member, which is obtained by pasting a sheet or

film on a substrate with the moisture-curable polyurethane hot-melt adhesive according to claim 1.

- 4 -